
PVA ADHESIVE SEALER

Supplied by: W.P. NOTCUTT LIMITED,
HOMEWOOD FARM, NEWARK LANE,
RIPLEY, SURREY, GU23 6DJ, ENGLAND

TELEPHONE: 01483 223311
TELEFAX: 01483 479594

DESCRIPTION

PVA Adhesive Sealer has been developed as a high performance adhesive for assembly operation in the furniture industry i.e. finger jointing, edges bonding, carcass assembly and cold press lamination operations. It bonds a wide variety of sawn and plain woods, plus all the synthetic and naturally derived panel stocks (except cement/silicate board). PVA Adhesive Sealer features high wet tack, fast bond strength development.

MACHINE TYPES

All glue spreaders, brush and bottle applicators.

ADHESIVE TYPE:	Synthetic Resin Emulsion
COLOUR:	White.
BROOKFIELD VISCOSITY @ 20°C:	114 Poise Brookfield 7/20/20 degrees centigrade.
SOLIDS CONTENT:	63%
APPLICATION TEMP:	Ideally 20°C
CLEANING:	Water
pH:	4.6

HEALTH & SAFETY

Ingredients permitted in American F & DA Register, 21 CFR, 175.105. See Health & Safety Data Sheet.

STORAGE REQUIREMENTS

Store at temperature above 7°C to prevent damage by cold conditions. Rotate stock using oldest material first. Keep containers covered when not in use to prevent contamination by airborne dust. Storage life is 5 months from receipt of goods by customer

CAUTION

This product has been tested for a range of applications and uses. The product has been manufactured to our current quality assurance specification and is recommended for production trails. We however cannot guarantee the product's suitability or fitness for the specific purposes of the customer due to the variation likely in materials, production techniques, storage and end-use requirements. Before using the product in commercial production the customer must carry out thorough production and end-use testing with specific regard to ageing of the bond or coating.

Supplied by:

W.P. NOTCUTT LTD, HOMEWOOD FARM, NEWARK LANE, RIPLEY, SURREY, GU23 6DJ
TELEPHONE: 01483 223311 TELEFAX: 01483 479594