

---

# NOTCUTT CONCRETE

## RELEASE AGENT

---

Supplied by: W.P. NOTCUTT LIMITED TELEPHONE: 01483 223311  
HOMEWOOD FARM, NEWARK LANE, TELEFAX: 01483 479594  
RIPLEY, SURREY, GU23 6DJ

### DESCRIPTION

Notcutt Concrete Release Agent is a chemical release agent specially formulated to give easy release of plastic and thermoplastic mould liners providing high quality surface finishes to concrete.

**i.e. Polypropylene, ABS, Polyurethane, some latex and rubber moulds etc.**

### ADVANTAGES

- Notcutt Concrete Release Agent is suitable for use on plastic mould liners with excellent results.
- It is a suspension and sediment free, highly mobile liquid, which can be used in fine sprays without clogging the jets.
- There is no unpleasant odour, even when using a fine fog spray.
- Provides a quick, positive release of moulds, reducing labour costs and damage to moulds.
- Very economic coverage rates can be obtained without difficulty.
- It can be used with either grey or white cement and concrete incorporating pigments.
- Notcutt Concrete Release Agent may be used for metal or timber mould boxes holding the mould liner, allowing easy cleaning of all equipment.
- Retains its mobility at low temperatures.
- Drastically reduces the incidence of blowholes, surface blemishes and staining.
- It may be applied immediately prior to casting, or treated moulds may be left until apparently dry.

### PROPERTIES

Appearance: Pale yellow – low viscosity  
Specific Gravity: 0.878 @ 15°C  
Flash Point: 184°C  
(Pensky Martin Closed Cup)  
Viscosity: 32 cSt @ 20°C  
Freezing Point: -30°C  
Storage Life: Indefinite in manufacturer's sealed drums

### APPLICATION

- Notcutt Concrete Release Agent is ready for use and should not be diluted.
- It should be applied as thinly and evenly as possible for optimum performance.
- It can be applied to all types of mould system by spray, fine-haired brush, swab or roller.
- Excess should be removed. For the best and most economical performance, application by fine fog spray is recommended.
- It will not clog fine jets even at low temperatures.

### COVERAGE

35 to 65 m<sup>2</sup>/litre dependant on material type porosity, texture of surface and ambient temperature.

### STORAGE AND HANDLING

Notcutt Concrete Release Agent requires no special storage facilities.  
This type of material should be applied in well-ventilated areas.

Keep away from naked flames, electrical equipment, foodstuffs and children.

These materials do not constitute a health hazard and do not promote a dermatitic or carcinogenic reaction provided reasonable care is exercised according to Health & Safety Regulations.